

Labino® TrAc Light - White



PORTABLE | LIGHT WEIGHT | NO CABLES

MAKES IT BRIGHT

- Labino® TrAc Light White lamp has a unique *white* luminance, which makes it possible to see things that have not been possible before.
- The Labino® TrAc Light lamp contains the trigger ballast, battery and bulb in one housing, making it light, portable, and very flexible.
- The Labino® TrAc Light lamp is available in three important distinctions – floodlight, midlight or spotlight – each giving different beams and intensities. The spotlight has the greatest focus and is the most intense, and the floodlight has the widest beam. The midlight is in between.
- The Labino® TrAc Light obtains full power in 5-15 seconds and can be switched on and off whenever used, without pre-cooling.
- The lamp is shock proof and generates very little heat.
- You can use the lamp outdoors, even in the rain, as the lamp is IP65 certified.
- Labino® TrAc Light lamps are based on two key components – the Labino DL-35 W Gas Discharge Bulb (MPXL-technology) and the Labino Trigger Ballast (Electronics). The interface technology between these key components creates unbeatable output performance.



TECHNICAL SPECIFICATION

Floodlight

Distribution angle (beam) 45°
Luminous flux: 3 500 lm

Midlight

Distribution angle (beam) 20°
Luminous flux: 3 500 lm

Spotlight

Distribution angle (beam) 3.5°
Luminous flux: 3 500 lm
Intensity > 750 000 cd

Handles

- Top Handle
- Pistol Handle
- Open Handle
- Mounting Brackets

Voltage

- 100, 115 and 230 VAC
- Input Power: 43 W
- Output Power: 35 W

Battery

- 14.8 V Li-ion accumulator
- Running time: 1.3 hr +/- 5%
- Charging time: approx. 3 hrs
- First time charge: 8 hrs

Additional Information

- Weight: 2.32 kilos
- Mechanical Stability (bulb): IEC810
- Service life (bulb): approx. 5 000 hrs
- Start-up time: full power after 5-15 sec
- Material in housing: anodized aluminium, plastics PA6-30
- The housing is via pre milled slots prepared for mounting devices
- S, CE, ETL/cETL approved
- IP65 classified, dust and temporary water jetting proof

DISTRIBUTOR:



Xspec Technology Sdn Bhd
No. 8 Jalan Industri USJ 1/8, Taman perindustrian USJ1
47600 Subang Jaya, Selangor, Malaysia
Tel: +60 3 8023 1161 Fax: +60 3 8023 1167
Email: inquiry@xspec.com.my
<http://www.xspec.com.my>