

# Labino® TrAc Pack Standard - White



## POWERFUL | BATTERY OPERATED

## MAKES IT BRIGHT

- Labino® TrAc Pack Standard White lamps have a unique *white* luminance, which makes it possible to see things that have not been possible before.
- The Labino® TrAc Pack Standard is a two-part lamp consisting of a light weight luminary unit and a ballast unit (electronics and battery).
- The Labino® TrAc Pack Standard lamp is available in three important distinctions – floodlight, midlight or spotlight – each giving different beams and intensities.
- The Labino® TrAc Pack Standard obtains full power in 5-15 seconds and can be switched on and off, without the need for pre-cooling.
- The lamp is shock proof and generates very little heat.
- You can use the lamp outdoors, even in the rain, as the lamp is IP65 certified.
- Labino® TrAc Pack Standard lamps are based on two key components – the Labino DL-35 W Gas Discharge Bulb (MPXL-technology) and the Labino Trigger Ballast (Electronics). The interface technology between these key components creates unbeatable output performance.



TrAc Pack Standard

## TECHNICAL SPECIFICATION

### Floodlight

Distribution angle (beam) 45°  
Luminous flux: 3 500 lm

### Midlight

Distribution angle (beam) 20°  
Luminous flux: 3 500 lm

### Spotlight

Distribution angle (beam) 3.5°  
Luminous flux: 3 500 lm  
Intensity > 750 000 cd

### Voltage

- Charger: 100, 115, 230 VAC
- Internal Battery: 12/24 VDC
- Input Power: 43 W
- Output Power: 35 W

### Weight

- Luminary Unit: 1.2 kilos
- Battery and Electronic Unit: 4.4 kilos

### Cables

- Between Luminary and Battery/Electronic Unit: 2.3 meters

### Battery

- 12 V, 7.2 Ampere, Lead
- Running time: 1.2 hours +/- 5%
- Charging time: 5-8 hours
- First time charge: 8 hours

### Additional Information

- Mechanical Stability (bulb): IEC810
- Service life (bulb): approx. 5 000 hrs
- Start-up time: full power after 5-15 sec
- Material in housing: anodized aluminium, plastics PA6-30
- The housing is via pre milled slots prepared for mounting devices
- S, CE, ETL/cETL approved
- IP65 classified, dust and temporary water jetting proof

### DISTRIBUTOR:



Xspec Technology Sdn Bhd  
No. 8 Jalan Industri USJ 1/8, Taman perindustrian USJ1  
47600 Subang Jaya, Selangor, Malaysia  
Tel: +60 3 8023 1161 Fax: +60 3 8023 1167  
Email: inquiry@xspec.com.my  
<http://www.xspec.com.my>