



PORTABLE
V I D E O
SYSTEMS

SEARCH

Search System | Part #WA-PSW11

System Contents:

WM-4 WalkAbout II™ - 5" LCD Display

LLC-1.4 - Low Light Color Camera

T-FNS-11 - 11' Telescoping Pole

BAT-2 - Two (2) NiMH Rechargeable Batteries

WBC - Battery Charger (Power Supply not shown)

S9-CASE - Carrying Case for wand or pole (not shown)

W-CASE - Carrying Case for all other components

WUH - Universal Chest Harness

Sunshade, A/V Cable & Vehicle Power Adapter not shown

Recommended Additions:

Videoscope

Gain visual access into rooms or compartments through openings as small as 1/4" (6mm).

Baton

2 Foot fixed length pole for access in confined spaces.

D-BAT

Allows use of alkaline 'D' cells when the rechargeable batteries are not charged. Good for emergency situations.

SYSTEM PART NUMBERS:

WA-PSW-W¹

DISPLAYS

WS=Detached WalkAbout
WA=Standard WalkAbout

POLES

W=5' Fixed length wand
11=11' Telescoping Pole

1) Add a **"-P"** to system part number to specify a PAL (European TV standard) system.



W-CASE



S9-CASE



T-FNS-11



STANDARD WALKABOUT



LLC-1.4



(2) BAT-2



WBC



WUH

ALTERNATE DISPLAY CONFIGURATIONS



DETACHED WALKABOUT



**PORTABLE
VIDEO
SYSTEMS**

Search System Specifications

WA-PSW-W¹ | WA-PSW-11¹

WalkAbout II Monitor

Display Size & Weight	Detached WalkAbout: 6.5"W x 7.0"H x 2.2"D / 2.1 lbs. (LCD); 5.0"W x 3.5"H x 3.5" D/2 lbs. (Base) Standard WalkAbout: 6.5"W x 9.0"H x 5.5"D / 3.65 lbs.
Construction	Rubber encapsulated aluminum case for shock resistance and weatherproofing
Display Size	5 inches measured diagonally
Resolution	960 dots (H) x 234 lines (V)
Operating Temperature	-20°C to 70°C
LCD Controls	Brightness, Contrast, Color, Tint, OFF/Mirror left/right & up/down
Mounting Options	Display can be worn on vest, belt or harness; detached display can also be hand held
Video Format	Auto switches between NTSC (American) or PAL (European)
Charger	12VDC from either power supply or vehicle adapter
Batteries	NiMH, 7.2V, 2.7AH
Discharge Time	2 hrs. with LEDs off
Charge Time	2 hrs. when fully discharged
Base Controls & Indicators	On/Off; LED intensity; Low battery
Connections	Camera (pole), A/V output, DC input (7.2V to 12V)

Cameras

Model	LLC-1.4
Construction	Submersible enclosure with hard-coated window
Size & Weight	1.4"D x 2.8"L / 0.2 lbs.
Features	6 Bright white LED illuminated, color camera, 270K pixels (320K/PAL), .03 lux, 6.0 mm, 53° FOV

Cases

Model	W-CASE	S9-CASE
Stores	WalkAbout II, camera and accessories	T-FNS-11
Construction	Rugged, watertight, plastic carry case with foam inserts having compartments for all components.	Soft padded carry case for pole.
Size	21" x 16" x 8"	48" x 8" x 2S"
Weight loaded	17 lbs.	5 lbs.

Poles

Model	W-FNS	T-FNS-11
Part of System	WA-PSW-W	WA-PSW-11
Construction	Single section fixed length fiberglass pole with foam grip	3 Section fiberglass telescoping
Collars	None	Rugged, break-proof, easy grip, twist collars for each pole section.
Articulation	1 foot flexible gooseneck can be flexed into any position	
Collapsed Length	4 feet collapsed and folded	
Extended Length	5 feet	11 feet
Weight	2 lbs.	4 lbs.